

GSM RTU 5015



The GSM RTU5015 controller is a simple but a powerful controller and can be used to turn devices remotely ON/OFF with a simple telephone call with first ring

Maximum 64 GSM Telephone numbers can be stored in RTU5015 as an authorized numbers/caller ID. Due to GSM technology calls made from these authorized numbers are free and there is no call cost

The GSM RTU5015 will rejects the calls made from any other telephone numbers other then the numbers are stored/authorized

FEATURES

- All functions are programmable with simple SMS command
- Simple Relay Control ON / OFF with free call to device
- Two digital inputs programmable to send SMS message
- Suitable to use as simple Alarm unit with various optional sensors
- Use your GSM Telephone for Gate Opener with free call

SUITABLE

- Irrigation, Telemetry
- Switch Appliances
- Shutters, Warehouses, Gates, Parking
- Home and Garage doors
- M2M
- Simple Alarm applications

Specifications

Power	DC 12V/2A
Power consumption	12V input Max. 50mA/Average 50mA
Frequency range	Dual band 900/1800 MHz
SIM Card	Supporting 3V SIM Card
Antenna	50 SMA Antenna Interface
Temperature range	-20 - +60C
Humidity Range	Relative humidity 90% (condensation free)
Relay, Rating	Single relay 3A/240VAC
Exterior Dimension	110mm*90mm*40mm
Net Weight	600 g



5/251 Blackburn Rd., Mt Waverley VIC 3149 Australia
PO Box 184, Mt Waverley VIC 3149 Australia
Tel +61 (03) 98879100 Fax +61 (03) 98868500
Web: www.unicompl.com Email: sales@unicompl.com