

RT-760

2 AND 4 LINE
ALPHANUMERIC PAGER

UNICOM



- :: 2 Line Display 2 x 15, 4 Line Display 4 x 20
- :: Message capacity dynamic 25,000 Characters
- :: Smart graphic LCD screen 112 x 32 dots
- :: Adjustable LCD contrast
- :: Personal message, mail drop, notebook
- :: 6 Cap Code ID each frame independent
- :: Programmable alerts for each cap code
- :: Optional Rubberized or IP54 Rugged Case
- :: Pocsag, Flex
- :: Selectable alert mode, 9 kinds of beep, 7 melodies, vibrate & silent, beep & vibrate
- :: Alert lengths 7, 14 sec, continuous beep and priority alert
- :: Alerts can be programmed independently for each cap code
- :: Alarm function, 3 sets of alarms with 10 event setting
- :: Automatic power on / off (silent receiving)
- :: Oldest message over written automatically by new message when memory is full
- :: Out of range indicator 0-9 minutes
- :: On Air programming
- :: Programmable both with PC / software and manually via keypad
- :: CE, FCC approval

SPECIFICATIONS

Radio Frequency	138-174, 278-286, 410-510, 928-932 MHz
Formats	Pocsag Flex
Sensitivity	512 bps: 5uv/m, 1200bps: 5 uv/m, 2400: 9uv/m
Channel Spacing	25kHz
Modulation	FSK-NRZ
Selectivity	>60 dB
Spurious Rejection	>60 dB
Image Rejection	>60 dB
Frequency Stability	Under 5 ppm (-10 ~ + 50C)
Power Supply	1.5V (AAA Type Alkaline)
Min. Operation Voltage	1.10 + / - 0.05V
Deviation	Mark - 4.5kHz, Space + 4.5kHz
Capcode (ID)	6 frame independent
Battery Life	4 - 5 weeks
Available Languages	English, German, Swiss, French, Russian, Spanish, Portuguese, Arabic Other languages on request
Dimension	68 x 47 x 17mm
Weight	50g (without battery)