

RT-950

NUMERIC POCSAG PAGER

UNICOM

Features



Perspective view



Standby display

- Synthesized
- 10 Alerts; Silent, (Vibration) Beep
- 6 capcode ID each frame independent
- 16 message memory
- 10 alphanumeric preprogrammed messages
- Lock up to 16 messages
- Delete individual or erase all messages
- Display; time, day and date
- Duplicate message indicator
- Message time stamping
- 3 alarm setting
- Low battery indicator
- Service area indicator
- Backlight

Specifications

Code Format	Pocsag
Radio Frequency	138-174, 278-286, 410-510, 928-932MHz Synthesized
Sensitivity	512 bps: 5 uv/m 1200 bps: 8 unv/m 2400 bps: 10 uv/m
Channel Spacing	25KHz / 138 - 174MHz 12.5KHz / 410-510MHz, 930MHz
Modulation / Deviation	FSK, NRZ / \pm 4.5KHz
Selectivity	More than 55db
Spurious Rejection	More than 40 db
Image Rejection	More than 40 db
Frequency Stability	10 ppm (-10 + 50C)
Power Supply	1.5V (AAA Alkaline)
Min. Operation Voltage	1.10 +-0.05V
Deviation	- 4.5KHz / + 4.5KHz
Capcode (ID)	6 sets frame-independent
Battery Life	approx 5 weeks
Dimension	60 x 41 x 18mm
Weight	40g (without battery)