
Wireless Transmitters & Receivers

800 / 900 MHz Suitable to use with MsgPro2010 or Stand Alone

Wireless Transmitters



EN1210 / EN1210W Universal wireless Transmitter easy connection for use any standard NO/NC contact or sensor. Fully supervised temper, low battery and inactivity. Available two models, standard, built-in magnetic reed switch



EN1223S Personal Pendant or wrist watch water resistance Transmitter with necklace and wrist band. Fully supervised for low battery and inactivity. Built in LED to indicate proper transmission



EN1233S Single button Personal Pendant Transmitter with necklace. Fully supervised for low battery and inactivity. Also suitable to be used for fixed position signalling



EN1233D Double button Personal Pendant Transmitter with necklace. Fully supervised for, low battery and inactivity. Also suitable to be used for fixed position signalling



EN1235S Personal Pendant Transmitter with belt clip. Fully supervised for low battery and inactivity Also suitable to be used for fixed position signalling



EN1235D Double button Personal Pendant Transmitter with Belt Clip. Fully supervised for, low battery and inactivity. Also suitable to be used for fixed position signalling



DS1235s-MD Man-down Personal Pendant Transmitter with belt clip. Fully supervised for tamper, low battery and inactivity



EN1235W Emergency Wall mount Call Box fixed position Transmitter. Fully supervised low battery, tamper and inactivity alarm. The ES1235W comes with LED backlit button for alarm transmission confirmation



EN1265 360 Degree Ceiling mount low current motion detector. Increased immunity to causes of false activation and low current detector is highly sensitive to moving infrared radiation. Increased immunity to causes of false activation. Fully supervised for tamper, low battery and inactivity



EN1260 Wall mount low current high-end applications. Highly sensitive to moving infrared radiation Increased immunity to causes of false activation. Fully supervised for tamper, low battery and inactivity

Wireless Receivers & Repeaters




EN4200 Serial Receiver, provides a wireless gateway between wireless transmitters and a head end application using RS-232 serial interface to MsgPro Messaging software



EN5000 Repeater is a sophisticated intelligent wireless Repeater/Receiver and range expander. Decodes and transmit signals from transmitters while ignoring the background noise. The EN5000 is ideal for large facilities such as multi floor buildings, shopping malls campuses and other open air installations. Virtually any number of repeaters can be added to a system scaling the system size as needed. Fully supervised for tamper, low battery and inactivity. Virtually any number of repeaters can be added to a system scaling the system size as needed. Fully supervised for tamper, low battery and inactivity. Available in optional weatherproof enclosure and a solar panel where no AC power is available



EN4204R, EN4216 Add-On Receivers with 4, 16 relay output. The receiver includes Form C relays for each output, allowing connection to any hardware panel or stand alone wireless applications



EN4232 is 32 Zone stand alone receiver with 12 open collector outputs. Outputs on all Receivers can be configured for latching, momentary or toggle modes independently. Wireless programming routine built into receivers