

Wireless Transmitters & Receivers

800 / 900 MHz Suitable to use with MsgPro2010 or as Stand Alone System

Wireless Transmitters



ENI215 / ENI210W Universal wireless Transmitter easy connection for use any standard NO/NC contact or sensor. Fully supervised tamper, low battery and inactivity. Available two models, standard and built-in magnetic reed switch



ENI223S Personal Pendant or wrist watch water resistance Transmitter with necklace and wrist band. Fully supervised for low battery and inactivity. Built in LED to indicate proper transmission



ENI233S Single Button Personal Pendant Transmitter with necklace. Fully supervised for low battery and inactivity. Also suitable to be used for fixed position signalling



ENI233D Double Button Personal Pendant Transmitter with necklace. Fully supervised for, low battery and inactivity. Also suitable to be used for fixed position signalling



ENI235S Personal Pendant Transmitter with belt clip. Fully supervised for low battery and inactivity. Also suitable to be used for fixed position signalling



ENI235D Double Button Personal Pendant Transmitter with Belt Clip. Fully supervised for, low battery and inactivity. Also suitable to be used for fixed position signalling



DS1235-MD and DS1235-MD-1 Man-down Personal Pendant Transmitter with belt clip. Fully supervised for tamper, low battery and inactivity. Available in standard or an industrial case



ENI235W Emergency Wall mount Call Box fixed position Transmitter. Fully supervised low battery, tamper and inactivity alarm. The ES1235W comes with LED backlit button for alarm transmission confirmation



ENI265 360 Degree Ceiling mount low current motion detector. Increased immunity to causes of false activation and low current detector is highly sensitive to moving infrared radiation. Increased immunity to causes of false activation. Fully supervised for tamper, low battery and inactivity



ENI260 Wall mount low current high-end applications. Highly sensitive to moving infrared radiation. Increased immunity to causes of false activation. Fully supervised for tamper, low battery and inactivity

Wireless Receivers & Repeaters



EN4200 Serial Receiver provides a wireless gateway between wireless transmitters and a head end application using RS-232 serial interface to MsgPro Messaging software



EN5000 Repeater is a sophisticated intelligent high power wireless Repeater Receiver and range expander. Decodes and transmit signals from transmitters while ignoring the background noise. The EN5000 is ideal for large facilities such as multi floor buildings, shopping malls, campuses and other open air installations. Virtually any number of repeaters can be added to a system scaling the system size as needed. Fully supervised for tamper, low battery and inactivity



EN4204R, EN4216 Receivers with 5, 16 Form C relay outputs or 5, 9, 12 open collector allowing each output to be connected to any panel or stand alone wireless applications



EN4232 is 32 Zone stand alone receiver with 12 open collector outputs and the **EN4232MR** with 12 relay outputs

Outputs on all Receivers can be configured in follower, latching, momentary or toggle modes



Available in optional weatherproof enclosure and a solar panel where no AC power is available